

Taiwan Eagle CCTV LTD



Taiwan EAGLE CCTV

REAL-TIME TRACKING

3G GPS SD-RECORDING H.264 MOBILE DVR (MODEL NO. HDVR04M-L)



Video Audio Alarm



Features

- H.264 codec-- smaller video size for storage/ remote connection
- VOIP
- Supporting USB 3G dongle (so there is no extra cost for 3g modem!)
- GPS built-in-chip, antenna optional
- Battery optional, so DVR could keep recording for 20 min after power loss.
- G-sensor record
- Auto backup driving record on SD card, for back-end evaluation
- Mobile phone/ PDA view

Model NO.	HDVR04M-L		
Video			
Operating system	Embedded Linux		
Camera inputs	BNC x4		
Outputs (main)	BNC x1, VGA x1		
Display resolution	NTSC – 720*480, PAL – 720*576		
Live frame rate	Up to 30 (NTSC) / 25 (PAL) IPS per camera		
Audio			
Inputs	RCA x1		
Outputs	RCA x1		
Record			
Compression	H.264		
Resolution & Frame rate	NTSC – 30 / 720*480, 60 / 720*240, 120/360*240, 720*288, 100 / 360*288		PAL – 25 / 720*576, 50 /
Record mode	Manual/Schedule/Alarm/Motion/Acceleration/Speed		
Pre-recording	0-10 sec.		
Post-recording	0-60 min.		
After power loss	20 min w/ optional battery		
Storage			
Internal storage	SD/SDHC (class10 is recommended)		
Backup	USB		
Event			
Alarm inputs	2		
Alarm outputs	1		
Network			
Interface	RJ45 or USB 3G dongle		
Remote view	IE, Firefox, free CMS, Mobile/PDA		
General			
Dimension and weight	13x12x5 cm, 0.5KG		
Built-in heater	-		
Operating temperature	0oC ~ +50oC (w/o internal lithium battery) 0oC ~ +45oC (w/ internal lithium battery) Lithium battery will not be charging over 40oC		
Power input	12 or +24VDC, with acceptable range +9.0~30VDC		
Power consumption	6W		
Operating shock	8G, 11ms (20 per five seconds max)		
Operating vibration	5~500Hz, 2.7G (0 to peak)		

* Spec is subject to changes without notices. 2011/10/07.