



CCTV PLASTIC IR DOME CAMERA



Features

- AGC
- BLC
- OSD
- 24pcs LED up to 20M
- 3-axis lens adjustment

MODEL NO.	PDS-540-3.6	PDS-420-3.6	PDA-420-3.6
Camera Sensor	1/3"SONY	1/3"SONY	1/4"SHARP
TV System		PAL/NTSC	
TVL	540 TVL	420 TVL	420 TVL
Pixels	PAL:752(H)×582(V) NTSC:768(H)×494(V)	PAL:500(H)×582(V) NTSC:510(H)×492(V)	PAL:500(H)×582(V) NTSC:510(H)×492(V)
Lens		Board Lens 3.6mm/F2.0	
Video Out		Composite Signal (1.0Vp-p, 75Ω)	
Sync		Internal	
Illumination	0.001 Lux/F2.0	0.005 Lux/F2.0	0.01 Lux/F2.0
S/N Ratio		≥ 48dB (AGC OFF)	
Gamma Correction		0.45	
Scanning System		PAL:625 Lines, 50 Field/Sec;NTSC:525 Lines, 60 Field/Sec	
Electronic Shutter Time		Auto:PAL 1/50-1/100,000Sec;NTSC 1/60-1/100,000Sec	
White Balance		Auto	
LED			
IR LED		φ 5X24PCS	
IR Series Distance		20M	
IR Status		Under 10 Lux By CDS	
IR Power On		CDS Auto Control	
POWER			
Power Source		DC12V 350mA	
ENVIRONMENT			
Operation Temperature		-10°C ~ +50°C RH95% Max	
Storage Temperature		-20°C ~ +60°C RH95% Max	
Dimension		φ 94 x 69(H) mm	
Weight		250g	

*Spec is subject to changes without notice. 2011/03/28.