



CCTV BULLET CAMERA



Features

- AGC
- BLC
- 24pcs LED up to 20M
- 3-axis bracket
- IP66 weather-proof

MODEL NO.	BS-540-3.6	BS-420-3.6	BA-420-3.6
Camera Sensor	1/3" SONY	1/3" SONY	1/4" SHARP
TVL	540TVL	420TVL	420TVL
Pixels	PAL:795(H)×596(V) NTSC:811(H)×508(V)	PAL:500(H)×582(V) NTSC:510(H)×492(V)	PAL:500(H)×582(V) NTSC:510(H)×492(V)
Lens		Board Lens 3.6mm/F2.0	
Video Out		Composite Signal (1.0Vp-p, 75Ω)	
Sync		Internal	
Illumination	0.001 Lux/F2.0	0.0005 Lux/F2.0	0.01 Lux/F2.0
S/N Ratio		≥ 48dB (AGC OFF)	
Gamma Correction		0.45	
Scanning System	PAL:625 Lines, 50 Field/Sec;NTSC:525 Lines, 60 Field/Sec		
Electronic Shutter Time	Auto:PAL 1/50-1/100,000Sec;NTSC 1/60-1/100,000Sec		
White Balance	Auto		
LED			
IR LED		φ 5 X24PCS	
IR Series Distance		20 M	
IR Status		Under 10 Lux By CDS	
IR Power On		CDS Auto Control	
POWER			
Power Source	DC12V 350mA (not included in the package)		
ENVIRONMENT			
Operation Temperature	-10°C ~ +50°C RH95% Max		
Storage Temperature	-20°C ~ +60°C RH95% Max		
Dimension	128(W) x90(H) x70(D)mm		
Weight	400g		

*Spec is subject to changes without notice. 2011/03/28.