



WEATHER-PROOF OUTDOOR TRUE D/N BULLET CAMERA



Features

- AGC. BLC. OSD
- 36pcs LED up to 50M
- Vari-focus 4-9mm
- Cable in the bracket
- IP66 weather-proof

MODEL NO.	US-600-0409	US-700-0409
Camera Sensor	1/3"SONY	1/3"SONY
TV System	PAL/NTSC	
TVL	600 TVL	700 TVL
Pixels	NTSC:811(H)×508(V) PAL:795(H)×596(V)	NTSC:1020(H)×508(V) PAL:1020(H)×596(V)
Lens	4-9mm Manual Zoom Lens	
Video Out	Composite Signal (1.0Vp-p, 75Ω)	
Sync	Internal	
Illumination	0.001 Lux/ F2.0	0.001 Lux/ F2.0
S/N Ratio	≥ 48dB (AGC OFF)	
Gamma Correction	0.45	
Scanning System	PAL:625 Lines, 50 Field/Sec;NTSC:525 Lines, 60 Field/Sec	
Electronic Shutter Time	Auto:PAL 1/50-1/100,000Sec;NTSC 1/60-1/100,000Sec	
White Balance	Auto	
LED		
IR LED	φ 8 X36PCS	
IR Series Distance	50M	
IR Status	Under 10 Lux By CDS	
IR Power On	CDS Auto Control	
POWER		
Power Source	DC12V, 150mA (dual power optional)	
ENVIRONMENT		
Operation Temperature	-10℃ ~ +50℃ RH95% Max	
Storage Temperature	-20℃ ~ +60℃ RH95% Max	
Dimension	260(W)×160(H)×105(D) mm	
Weight	1500g	

*Spec is subject to changes without notice. 2011/05/02.